

Brp102 Led55/740 Dm 42-60a

Kod Elektriko: 90394 Kod Philips: 8718696998175



Dane techniczne:

- Lamp family code LED55 [LED module 5500 lm]
- Light source color 740 neutral white
- Driver included Yes
- Driver/power unit/transformer **Power supply unit**
- Number of gear units 1 unit
- Connection Push-in connector and pull relief
- Luminaire light beam spread -
- Protection class IEC Safety class I
- CE mark CE mark
- Constant light output No
- Number of products on MCB of 16 A type B 11

Strona 1 z 2 info@elektriko.pl



- Input Frequency 50 to 60Hz
- Input Voltage 220 to 240V
- Inrush current 46A
- RoHS mark RoHS mark
- Dimmable No
- Housing Material Aluminum die-cast
- Optical cover/lens material Tempered glass
- Power Factor (Min) 0.98
- · Reflector material -
- Fixation material Aluminum
- Ingress protection code IP65 [Dust penetration-protected, jet-proof]
- · Optical cover/lens finish Clear
- Overall diameter 520mm
- Overall height 79mm
- Mech. impact protection code IK08 [5 J vandal-protected]
- Maximum dim level Not applicable
- Product family code BRP102 [CoreLine Malaga LED large]
- Optical cover/lens type Flat glass
- Light source engine type **LED**
- Mounting device Universal for diameter 42 to 60 mm adjustable
- Optical cover/lens shape Flat
- Overall length 493mm
- Overall width 217mm
- Effective projected area 0.22526m2
- Useful life L80B10 60000h

Product family information

The CoreLine Malaga LED family is designed for general Road, Street and Residential application. The family consists of two sizes and uses a Philips standardized design LED engine as light source and a Philips Xitanium fixed output outdoor driver. Quality you can rely on. CoreLine Malaga LED has been designed as efficient as possible, performing the same task as the SON-T 50, 70, 100 and 150W luminaires it replaces; provide the right amount of light in the right place. The medium beam (DM) optic delivers an efficient distribution onto the road. The combination results in interesting energy savings which reduce operating costs significantly. 50% energy reduction is realistically possible. At the same time, the investment in a CoreLine Malaga LED luminaire is on the same level as an old SON-T luminaire including the first lamp. As the LED light engine in CoreLine Malaga LED will last the life time of the luminaire, just by saving the multiple lamp replacements needed with SON-T will already return the investment in it. Ease of installation is obtained through the extended gland feature; the luminaire does not need to be opened to connect the power cable. At the same time, the flat glass cover can be removed to allow access to the driver for maintenance if required. Adding up the functions and features truly make a choice for CoreLine Malaga LED an easy decision. As a member of the CoreLine family, Malaga LED is easy and quick available thru Philips Partners near you. Simply efficient.

Features

Direct, one on one, replacement for SON-T lamps in Road, Street and Residential applications. Purpose, dedicated to LED, robust design including Philips standardized LED light platform and fixed output Philips Xitanium outdoor driver. Easy installation through the extended gland. No need to open the luminaire. 1000.000 hours working life L70B10 (or 60.000 hours L80B10).

Applications

General outdoor; Road, Street and Residential areasIndustrial areas or parking lots. Public transport such as bus or tramway stops.